
BSL-15A LED Light Source



Introduction

BSL-15A LED Light Source is designed as an auxiliary lighting device for stereo and other microscopes to get better observation results. The LED light source provides high quality illumination, long working life and saves energy.

Features

1. More stable power supply with CE standard electrical parts and circuit.
2. Reliable with stable structure.
3. Long working life and low noise.

Specification

Item	Specification	BSL-15A-1	BSL-15A-2	BSL-15A-O
Power Supplier	Input Voltage: 100V-240V/ 50-60Hz	•	•	•
	15W LED light lamp			
	Lamp Life: 50000 hours			
	The color temperature: 6000K			
	Illuminance: 90000Lx			
	Brightness Adjustable			

	Optical Fiber Interface: Φ16mm			
	Cooling: Built In Large-area Radiator and Cooling Fan			
	Size: 230mm×101.6mm×150mm			
	Gross Weight: 2.9 kgs (Optical Fiber not included)			
	Net Weight: 2.4 kgs (Optical Fiber not included)			
Single Light Guide	Single Rigid Fiber, length 550mm, diameter 8mm, with Condenser, 5/8" Standard Interface	●		
Dual Light Guide	Double Rigid Fiber, length 550mm, diameter 8mm, with Condenser, 5/8" Standard Interface		●	
Ring Light Guide	Ring Flexible Fiber, length 550mm, diameter 8mm, 5/8" Standard Interface, Adapter Ring Size Φ50mm/ Φ60mm			●
Package	1 set/carton, 285mm×230mm×255mm, 3kg	●	●	●
	4 sets/carton, 540mm*320mm*470mm, 12kg	●	●	●

Note: ● Standard Outfit, ○ Optional